

S P E C I F I C A T I O N S

ConferenceHub™ USB | 4-Port Ethernet Hub with USB Charging



Part Number: TA-6535-A01

The TeleAdapt ConferenceHub™ just got a whole lot more powerful.

Now users can charge their mobile devices! For years the ConferenceHub has been the cleanest way to provide wired internet connections to the conference room table.

Now on top of the 4 retractable ethernet cables, the ConferenceHub provides 4 USB ports. 3 x 1 Amp and 1 x 2.1 Amp designed especially for tablets. Setup is as simple as plugging into power, and connecting a live internet feed via a single CAT5 type connection. Now you can connect to the internet and charge your mobile devices.

Don't let a dead battery slow down your meetings, and don't make your guests get down on the floor to access power or internet. ConferenceHub USB - the ultimate conference room accessory.

- Features 4 integrated retractable ethernet cables per unit... or daisy-chain up to four hubs together to provide up to 16 wired connection points.
- 3 x 1 Amp and 1 x 2.1 Amp USB ports
- Plug-and-play network setup
- Allows for multiple, concurrent use of the network from one point
- Enhance the look of conference or meeting rooms & increase productivity
- Retractable cable function eliminates cable clutter



web: www.tsochospitality.com
email: teleadapt@tsoc.com
phone: 1-888-258-8762

S P E C I F I C A T I O N S

ConferenceHub™ USB | 4-Port Ethernet Hub with USB Charging

Part Number: TA-6530-A01



Features & Benefits

- 4 x 2m (6ft) CAT5e LAN (10/100Mbps) retractable cords with Ethernet connectors
- 4 USB ports, 3 x 1 Amp, 1 x 2.1 Amp
- Auto-learning of networking configurations
- Daisy-chain multiple units for more connection points
- Status lights informs users when the network is on-line and available for use
- Full-duplex 100Mbps bandwidth on each port
- IEEE 802.3x flow control for full-duplex communication
- Plug-and-play connections in all environments, PSU with US/EU/UK tips

Technical Specifications

- Standards: IEEE 802.3 10BASE-T, IEEE 802.3u, 100BASE-TX
- 4 CAT5e (10/100Mbps) cords at extended length of 2M (6ft)
- Network Transmission Media: 10Base-T Cat. 3,4,5 UTP/STP
100BASE-TX Cat.5 UTP/STP
- Power Adapter: DC 7.5V
- Network Status Monitoring LEDs perport: LINK/ACT, 10/100M
- FDX System: POWER
- BUFFER MEMORY: 768KByte per device
- MAC Address: Up to 2K per device
- Power Consumption: 2 watts (Maximum)
- Operating Temperature: 0 - 55 Celsius
- Humidity: 10% - 90% RH



web:
email:
phone:

www.tsochospitality.com
teleadapt@tsoc.com
1-888-258-8762

ConferenceHub USB