teleadapt

ChargePort Pro TA-7820US

Desktop power and charging for hotel guest rooms.



Sleek, Stylish Design

ChargePort Pro is sleek and stylish to blend easily with your décor choices and is available in either black or grey. Use of the latest integrated GaN power supply technology ensures minimum size and maximum efficiency and power output.





Dual Mains Outlets and Qi

ChargePort Pro features dual tamper resistant (TR) US 120V NEMA-5 mains outlets which are rotated to maximise flexibility and can supply a total of up to 10A.

The top surface has an integrated 10W Qi wireless charging pad. Simply place your Qi compatible smartphone on the charging pad to enable charging.



Triple USB Charging

Dual USB-C outlets can charge up to 45 watts (shared) for smartphones, tablets and laptops. In addition charge at up to 12W using USB Type-A which is ideal for charging smartphones and tablets.



Passthrough Mains Plug

The passthrough mains plug means you don't lose use of a mains outlet when you plug ChargePort Pro in.



Security Options

For additional security choose from a cable clamp, adhesive pad or security lanyard.



web: email: phone: www.tsochospitality.com hospitality@tsoc.com 1-888-258-8762

Specifications

- Durable construction designed for everyday use.
- 2 x US, tamper resistant, NEMA-5 outlets, 120V, 10A shared max.
- Rotated mains outlet layout for maximum flexibility.
- Integrated GaN power supply for minimum size and maximum efficiency and power.
- 10W Qi Certified wireless charging pad with Foreign Object Detection (FOD).
- 2 x USB-C charging sockets, PD/PPS.

Single use:

USB-C1: 5V/3A, 9V/3A, 15V/3A, 20V/2.25A. PPS: 5V-16V/3A, 5V-21V/2.25A (45W Max).

USB-C2: 5V/3A, 9V/3A, 15V/3A, 20V/2.25A. PPS: 5V-16V/3A, 5V-21V/ 2.25A (45W Max).


Dual use:

USB-C1: 5V/3A, 9V/3A, 15V/2A, 20V/1.5A. PPS:5V-11V/3A (30W Max). USB-C2: 5V/3A,9V/1.67A (15W).

- 1 x USB-A charging socket. 5V, 2.4A.
- 67W maximum, 2 x USB-C 45W (shared),1 x USB-A 12W, 10W Qi.
- Input 120V, 15A with integrated mains cable.

- Built-in overload protection.
- Pass-through plug replaces wall outlet used to install.
- Certified by ETL to UL962A including spill test and CSA 22.2. Also FCC part 15, sub part b and WPC Qi 1.3.
- Security options include cable clamp, adhesive pad and security lanyard.

Dimensions



- A. 2 x US NEMA-5, tamper resistant outlets.
- B. 10W certified Qi charging pad.
- C. 2 x USB-Type-C® and 1 x USB-A charging.

Part Numbers

TA-7820US-D8-AS

ChargePort Pro, with passthrough US plug, Black, 8FT.

TA-7820US-D8-BS

ChargePort Pro, with passthrough US plug, Black/Grey, 8FT.

